

CP-UVR-0401E1-S**4 Ch. 1080P Lite Cosmic HD DVR****COSMIC**
HD DVR**Main Features**

- Auto Adaptive HDCVI/AHD/TVI/CVBS signals
- Support upto 5MP IP Camera
- All channel 1080P Lite Realtime Recording
- H.264 dual-stream Video Compression
- HDMI / VGA Simultaneous Video Output
- Support 1 SATA HDD up to 6TB, 2 USB2.0
- Mobile Software: iCMOB, gCMOB
- CMS Software:KVMS, KVMS Pro



CP-UVR-0401E1-S

4 Ch. 1080P Lite Cosmic HD DVR

COSMIC
HD DVR

Feature

Processor
Operating System
IP Camera Input
Two-way Talk
User Interface
Video Input
Video Output
Video Standard
Compression
Video Resolution
Video Recording
Video Display Split
Audio Input
Audio Output
Motion Detection
Video Loss
Camera Blank
Smart Phone
Hard Disk
Trigger Events
Recording Mode
Search Mode
Playback
Backup Mode
Max User Account
Record Interval
Interface Ports
Ethernet

Specification

Embedded processor
Embedded LINUX
4+1: each channel up to 2MP
Reuse audio in/out, RCA
GUI
4 channel, BNC
1 HDMI, 1 VGA
Analog: NTSC(525Line, 60f/s), PAL(625Line, 50f/s)
H.264
1920 × 1080, 1280 × 1024, 1280 × 720, 1024 × 768
Main Stream: 1080N/720P/960H/D1/HD1/BCIF/CIF/QCIF (1~25/30fps), Extra Stream: D1/CIF/QCIF(1~25/30fps)
1/4/6
1 channel, RCA
1 channel, RCA
Supports
Supports
Supports
iPhone, iPad, Android, Phone
1 SATA port, up to 6TB
Recording, PTZ, Tour, Alarm Out, Video Push, Email, FTP, Snapshot, Buzzer and Screen Tips
Manual, Schedule (Regular, Continuous), MD (Video detection: Motion Detection, Video Loss, Tampering), Alarm, Stop
Time /Date, Alarm, MD and Exact Search (accurate to second)
Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous camera, Full screen, Repeat, Shuffle, Backup selection, Digital zoom
USB Device/Network
128 users
1~60 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec
1 HDMI, 1 VGA, 2 USB2.0, 1 RS485
RJ-45 port (10/100M)



CP- UVR-0401E1-S

4 Ch. 1080P Lite Cosmic HD DVR

COSMIC
HD DVR

Feature

Protocols

Power Supply

Power Consumption

Working Temp

Dimensions

Weight

Specification

HTTP, TCP/IP, IPv4/IPv6, UPnP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPoE, DDNS, FTP, Alarm Server, P2P, IP Search, ONVIF 2.4.1, CGI Conformant

DC12V/2A

<10W(without HDD)

-10 ~+55°C / 10~90%RH / 86~106kpa

260mm ×236mm ×48mm

0.75KG(without HDD)