

CP- UVR-0401E1S-V4**4 Ch. 1080P Lite Cosmic HD DVR****Main Features**

- Auto Adaptive HDCVI/AHD/TVI/CVBS/IP signals
- Support upto 2MP IP Camera
- All channel 1080P Lite Realtime Recording
- Support 1 SATA HDD up to 8TB, 2 USB Ports(2.0)
- HDMI / VGA Simultaneous Video Output
- H.264 dual-stream Video Compression
- Mobile Software: iCMOB, gCMOB
- CMS Software: KVMS, KVMS Pro





CP-UVR-0401E1S-V4

4 Ch. 1080P Lite Cosmic HD DVR



Feature

Processor
IP Camera Input
Operating System
Two-way Talk
User Interface
Video Input
Video Output
Compression
Video Resolution

Video Recording

Video Display Split
Audio Input
Audio Output
Motion Detection
Video Loss
Camera Blank
Smart Phone
Hard Disk
Trigger Events

Recording Mode

Search Mode

Playback

Backup Mode
Interface Ports
Max User Account
Record Interval
Ethernet

Specification

Embedded processor
4+1 Ch. :each channel up to 2MP
Embedded LINUX
Reuse audio in/out, RCA
GUI
4 channel, BNC
1 HDMI, 1 VGA
H.264
1920 × 1080, 1280 × 1024, 1280 × 720, 1024 × 768

Main Stream: 1080N/ 720P/ 960H/ D1/ HD1/ BCIF/ CIF/ QCIF (1~25/30fps), Sub stream: CIF/ QCIF(1~15fps)

1/4/6
1 channel, RCA
1 channel, RCA
Supports
Supports
Supports
iPhone, iPad, Android Phone
1 SATA port, up to 8TB
Recording, PTZ, Tour, Alarm Out, Video Push, Email, FTP, Snapshot, Buzzer and Screen Tips
Manual, Schedule (Regular, Continuous), MD (Video detection: Motion Detection, Video Loss, Tampering), Alarm, Stop
Time /Date, Alarm, MD and Exact Search (accurate to second)

Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous camera, Full screen, Repeat, Shuffle, Backup, selection, Digital zoom

USB Device/Network
1 HDMI, 1 VGA, 2 USB Ports(2.0)
128 users
1~60 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec
RJ-45 port (10/100M)



CP- UVR-0401E1S-V4**4 Ch. 1080P Lite Cosmic HD DVR****Feature**

Protocols

Power Supply

Power Consumption

Working Temp

Dimensions

Weight

Specification

HTTP, TCP/IP, IPv4/IPv6, UPnP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPoE, DDNS, FTP, Alarm Server, P2P, ONVIF Version 2.4 conformance

DC12V/2A

<10W (Without HDD)

-10°C ~ +55°C/ 0 ~ 90% RH

205mm x 211mm x 45mm

0.55kg (without HDD)